

Reference Numbers

Commonly Used Reference Numbers

* = Number of cores

0282	2 core, circular PCP sheathed Miners' cap lamp flexible cord	2812X	Flat parallel twin, PVC insulation, 300/300v BS6500, flexible cord
0361	Welding cable, tinned copper conductor, vulcanised rubber insulation/tough rubber sheath. BS638.	309*Y	Circular, PVC heat resistant insulation sheathed 300/500v BS6500, flexible cord.
0361TQ (PC)	Welding cable, plain copper conductor, EPR insulation/CSP sheathed. BS638.	318*	Circular, vulcanised rubber insulation/tough rubber sheathed, 300/500v BS6500, flexible cord.
0361 (AL)	Welding cable, aluminium conductor, vulcanised rubber insulation/tough rubber sheathed. BS638.	318*Y	Circular, PVC insulation/PVC sheathed 300/500v BS6500, flexible cord.
0361TQ (AL)	Welding cable, aluminium conductor, EPR insulation/CSP sheathed. BS638.	318*P	Circular, vulcanised rubber insulation/PCP sheathed, 300/500v BS6500, flexible cord.
044*Y	Microphone cable, PVC insulation/PVC sheathed (special thickness).	318*TQ	Circular, EPR insulation/CSP sheathed 300/500v BS6500, flexible cord.
2023	3 core, twisted, vulcanised rubber - cotton braid insulation 300/300v BS6500, flexible cord.	318*DD	Circular, silicone rubber insulation/silicone rubber sheathed, 300/500v BS6500, flexible cord.
204*	Circular, vulcanised rubber insulation/cotton braid sheathed 300/300v BS6500, flexible cord.	3192Y	2 core, PVC insulation/PVC sheathed, flat 300/500v BS6500, flexible cord.
2093Y	3 core, PVC heat resisting insulation/PVC heat resisting sheathed. Circular, 300/300v BS6500, flexible cord.	322*Y	Circular, PVC insulated/PVC sheathed/galv. mild steel spiral interlocking armour - with or without PVC sheath 300/500v BS6500, flexible cord.
218*Y	Circular, PVC insulation/PVC sheathed. 300/300v BS6500, flexible cord.	326*Y	Circular, PVC insulation/PVC bedded/galv. mild steel wire braid/PVC sheathed, 300/500v BS6500, flexible cord.
2192Y	2 core, PVC insulation/PVC sheathed Flat 300/300 v. BS6500, flexible cord.	367*	Circular, vulcanised rubber insulation/non metallic braided, lift flexible, 300/500v BS6977, flexible cord.
2213	3 core, vulcanised rubber insulation/tough rubber sheathed/cotton braid, 300/300v BS6500, flexible cord.	380*Y	Circular, PVC insulation/PVC bedded/plain copper wire braid screened/PVC sheathed, 300/500v BS6500, flexible cord.
2491X	Single core, PVC insulation 0.5 sq.mm, 300/500v BS6500, 1.5sq.mm - 4 sq.mm, 450/750 v.g. BS6004, flexible cord	380*P	Circular, vulcanised rubber insulation/tough rubber sheathed/tinned copper wire braid screened/PCP sheathed, 300/500v BS6500, flexible cord.
2492X	Two 2491X twisted, flexible cord	380*TQ	Circular, EPR insulation/CSP bedded/tinned copper wire braid screened/CSP sheathed, 300/500v BS6500, flexible cord.
2771D	Single core, silicone rubber, glass fibre braid insulation 300/500v BS6500, flexible cord.	398*	Heavy duty circular, vulcanised rubber insulation/PCP sheathed 450/750v BS6007, flexible cord
2782D	Two 2771D twisted flexible cord.	6101T	Single core, EPR - braided and compounded insulation 450/750v BS6007, wiring cable.
279*D	Circular, silicone rubber insulation/glass fibre braid sheathed 300/500v BS6500, flexible cord.		

Reference Numbers

Commonly Used Reference Numbers

618*Y	Circular, PVC insulation/PVC sheathed 1 sq. mm. - 35 sq. mm. 300/500v BS6004. 50 sq. mm. - 630 sq. mm. gen in acc BS6346, wiring cable.	680*TQ	Circular, EPR insulation/CSP bedded/tinned copper wire braid screen/CSP sheathed, 450/750v gen to BS6007, flexible cord.
6192P	2 core, vulcanised rubber insulation/PCP sheathed Flat 300/500v BS6007, festoon wiring cable.	694*X	Circular, PVC insulation/PVC bedded/single steel wire armoured/PVC sheathed 600/1000v BS6346, mains wiring cable.
619*Y	Flat, PVC insulation/PVC sheathed 300/500v BS6004, wiring cable.	694*X (S)	As 694*X but with shaped conductors.
624*Y	Flat, PVC insulation - laid up in parallel with a bare ECC within one interstice/PVC sheathed 300/500v BS6004, wiring cable.	H07V-R	Single core, PVC insulation 4 sq. mm. - 400 sq. mm, 450/750v to BS6004.
638*Y	Circular, PVC insulation/PVC sheathed 300/500v gen in acc BS6004, flexible cord.	H07V-U	Single core, PVC insulation, 1.5 sq. mm - 2.5 sq. mm, (solid) 450/750v to BS6004.
638*TQ	Circular, EPR insulation/CSP sheathed, 450/750v BS6007, flexible cable.	H05V-U	Single core, PVC insulation, 1.0 sq. mm (solid) 300/500v to BS6004
638*DD	Circular, silicone rubber insulation/silicone rubber sheathed 450/750v BS6007, flexible cable.	H05RR-F	Circular, vulcanised rubber insulation/tough rubber sheathed. 300/500v to BS6500
6491X	Single core, PVC insulation 1 sq. mm. - 630 sq. mm. 450/750v BS6004	H03VV-F	Circular, PVC insulated/PVC sheathed, 300/300v to BS6500.
657*TQ	Circular, EPR insulation/CSP sheathed 600/1000v BS6883, shipwiring cable. (circular conductors)	H03VVH2-F	Flat 2 core, PVC insulated/PVC sheathed, 300/300v to BS6500
657*TQ (S)	As 657*TQ but with shaped conductors	H05VV-F	Circular, PVC insulated/PVC sheathed, 300/500v to BS6500
658*TQ	Circular, EPR insulation/CSP bedding/galv. mild steel wire braid armour/CSP sheathed. 600/1000v BS6883, shipwiring cable (circular conductors)	H05VVH2-F	Flat, 2 core, PVC insulated/PVC sheathed, 300/500v to BS6500
658*TQ (S)	As 658*TQ but with shaped conductors.	H05V-K	Single core, PVC insulation 0.5 sq. mm - 1.0 sq. mm, 300/500v to BS6500.
659*TQ	Circular EPR insulation/CSP bedded/tinned phospher bronze braid armour/CSP sheathed 600/1000v BS6883, shipwiring cable (circular conductors).	H07V-K	Single core, PVC insulation, 1.5 sq. mm - 2.5 sq. mm, 450/750v to BS6004.
659*TQ (S)	As 659*TQ but with shaped conductors	H07RN-F	Circular, rubber insulated/rubber sheathed, 450/750v to BS6007.
6701X	Single core, PVC insulation 450/750v BS 6004, flexible cord.	SIF	Silicone insulated single core flexible 300/500v
		SIHF	Silicone rubber insulated/Silicone rubber sheathed, 300/500v
		(AL)	To denote aluminium conductors. To be added after other suffix, if used e.g. 6491X(AL) and 6242Y(AL).
		(S)	Shaped conductors.